

10/587448
IP20 Rec'd PCT/PTO 25 JUL 2006

中华人民共和国国家知识产权局
STATE INTELLECTUAL PROPERTY OFFICE
OF THE PEOPLE'S REPUBLIC OF CHINA



证 明

CERTIFICATE

本证明之附件是向中国专利局作为受理局提交的下列国际申请副本
TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY OF THE BELOW
IDENTIFIED INTERNATIONAL APPLICATION THAT WAS FILED WITH THE
CHINESE PATENT OFFICE AS RECEIVING OFFICE

请 号: PCT/CN2004/000220

ONAL APPLICATION NUMBER

请 日: 18. MAR 2004 (18.03.2004)

ONAL FILING DATE

名 称: METHOD AND APPARATUS TO SUPPORT BOOTING

VENTION DESPITE DEFICIENT RESOURCES

CERTIFIED COPY OF
PRIORITY DOCUMENT

中华人民共和国国家知识产权局局长

COMMISSIONER OF THE STATE INTELLECTUAL PROPERTY
OFFICE OF THE PEOPLE'S REPUBLIC OF CHINA

二零零六年五月十一日

MAY 11, 2006

P4107/BST

1/4

PCT REQUEST

Original (for SUBMISSION)

0	For receiving Office use only	
0-1	International Application No.	PCT/CN2004 / 0 0 0 2 2 0
0-2	International Filing Date	1 8 · MAR 2004 (1 8 · 0 3 · 2 0 0 4)
0-3	Name of receiving Office and "PCT International Application"	RO/CN 中华人民共和国国家知识产权局 PCT International Application
0-4	Form - PCT/RO/101 PCT Request	
0-4-1	Prepared Using	PCT-SAFE [EASY mode] Version 3.50 (Build 0002.158)
0-5	Petition The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty	
0-6	Receiving Office (specified by the applicant)	China Intellectual Property Office (RO/CN)
0-7	Applicant's or agent's file reference	P4107/BST
I	Title of Invention	METHOD AND APPARATUS TO SUPPORT BOOTING DESPITE DEFICIENT RESOURCES
II	Applicant	
II-1	This person is:	applicant only
II-2	Applicant for	all designated States except US
II-4	Name:	INTEL CORPORATION
II-5	Address:	2200 Mission College Boulevard, Santa Clara, California 95052 United States of America
II-6	State of nationality	US
II-7	State of residence	US
III-1	Applicant and/or inventor	
III-1-1	This person is:	applicant and inventor
III-1-2	Applicant for	US only
III-1-4	Name (LAST, First)	CHEN, Lechong
III-1-5	Address:	N31 Apt. 1003 Lane 1555 Kai Xuan Road 200000 Shanghai China
III-1-6	State of nationality	CN
III-1-7	State of residence	CN

P4107/BST

2/4

PCT REQUEST

Original (for SUBMISSION)

III-2	Applicant and/or inventor	
III-2-1	This person is:	applicant and inventor
III-2-2	Applicant for	US only
III-2-4	Name (LAST, First)	XIANG, Ma
III-2-5	Address:	N20 Apt. 501 400 Gui Lin West Road 200000 Shanghai China
III-2-6	State of nationality	CN
III-2-7	State of residence	CN
III-3	Applicant and/or inventor	
III-3-1	This person is:	inventor only
III-3-4	Name (LAST, First)	CHEN, Lechong
III-3-5	Address:	N31 Apt. 1003 Lane 1555 Kai Xuan Road 200000 Shanghai China
III-4	Applicant and/or inventor	
III-4-1	This person is:	inventor only
III-4-4	Name (LAST, First)	XIANG, Ma
III-4-5	Address:	N20 Apt. 501 400 Gui Lin West Road 200000 Shanghai China
IV-1	Agent or common representative; or address for correspondence The person identified below is hereby/ has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent
IV-1-1	Name:	KANGXIN & PARTNERS
IV-1-2	Address:	Suite 402 Block B, Tongtai Mansion, Jinrongdajie, Xicheng District, 100032 Beijing China
IV-1-3	Telephone No.	86-010-88087204
IV-1-4	Facsimile No.	86-010-88087200
IV-1-5	e-mail	gpliu@vip.sina.com
IV-1-6	Agent's registration No.	11240

* ROICN

P4107/BST

3/4

PCT REQUEST

Original (for SUBMISSION)

V	DESIGNATIONS		
V-1	The filing of this request constitutes under Rule 4.9(a), the designation of all Contracting States bound by the PCT on the international filing date, for the grant of every kind of protection available and, where applicable, for the grant of both regional and national patents.		
VI-1	Priority Claim	NONE	
VII-1	International Searching Authority Chosen	China Intellectual Property Office (ISA/CN)	
VIII	Declarations	Number of declarations	
VIII-1	Declaration as to the identity of the inventor	-	
VIII-2	Declaration as to the applicant's entitlement, as at the international filing date, to apply for and be granted a patent	-	
VIII-3	Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application	-	
VIII-4	Declaration of inventorship (only for the purposes of the designation of the United States of America)	-	
VIII-5	Declaration as to non-prejudicial disclosures or exceptions to lack of novelty	-	
IX	Check list	number of sheets	electronic file(s) attached
IX-1	Request (including declaration sheets)	4	✓
IX-2	Description	10	-
IX-3	Claims	7	-
IX-4	Abstract	1	✓
IX-5	Drawings	3	-
IX-7	TOTAL	25	
	Accompanying Items	paper document(s) attached	electronic file(s) attached
IX-8	Fee calculation sheet	✓	-
IX-17	PCT-SAFE physical media	-	✓
IX-19	Figure of the drawings which should accompany the abstract	1	
IX-20	Language of filing of the international application	English	


P4107/BST

4/4

PCT REQUEST

Original (for SUBMISSION)

X-1	Signature of applicant, agent or common representative	
X-1-1	Name:	KANGXIN & PARTNERS
X-1-2	Name of signatory	Guoping LIU
X-1-3	Capacity	



FOR RECEIVING OFFICE USE ONLY

10-1	Date of actual receipt of the purported international application	18 · MAR 2004 (18 · 03 · 2004)
10-2	Drawings:	
10-2-1	Received	
10-2-2	Not received	
10-3	Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application	
10-4	Date of timely receipt of the required corrections under PCT Article 11(2)	
10-5	International Searching Authority	ISA/CN
10-6	Transmittal of search copy delayed until search fee is paid	

FOR INTERNATIONAL BUREAU USE ONLY


11-1	Date of receipt of the record copy by the International Bureau	
------	--	--

PCT (ANNEX - FEE CALCULATION SHEET)

Original (for SUBMISSION)

(This sheet is not part of and does not count as a sheet of the international application)

0	For receiving Office use only	PCT/CN 2004 / 0 0 0 2 2 0		
0-1	International Application No.			
0-2	Date stamp of the receiving Office	1 8 · MAR 2004 (1 8 · 0 3 · 2 0 0 4)		
0-4	Form PCT/RO/101 (Annex) PCT Fee Calculation Sheet	PCT-SAFE [EASY mode] Version 3.50 (Build 0002.158)		
0-4-1	Prepared Using			
0-9	Applicant's or agent's file reference	P4107/BST		
2	Applicant	INTEL CORPORATION		
12	Calculation of prescribed fees	fee amount/multiplier	Total amounts (CNY)	Total amounts (EQF)
12-1	Transmittal fee T	⇔	500	
12-2-1	Search fee S	⇔	1500	
12-2-2	International search to be carried out by	CN		
12-3	International filing fee (first 30 sheets) i1	1400 EQF		
12-4	Remaining sheets	0		
12-5	Additional amount (X)	0 EQF		
12-6	Total additional amount i2	0 EQF		
12-7	i1 + i2 = i	1400 EQF		
12-12	EASY Filing reduction R	EQF-100		
12-13	Total International filing fee (i-R) I	⇔		1300
12-14	Fee for priority document			
	Number of priority documents requested	0		
12-15	Fee per document (X)	150 CNY		
12-16	Total priority document fee: P	⇔		
12-17	TOTAL FEES PAYABLE (T+S+I+P)	⇔	2000	1300
12-19	Mode of payment	authorization to charge deposit account		



PCT

Original (for SUBMISSION)

13-2-3	Validation messages Names	Yellow Inventor 1: should be indicated as applicant/inventor for the purposes of the US designation.
	Validation messages Names	Yellow Inventor 2: should be indicated as applicant/inventor for the purposes of the US designation.
	Validation messages Names	Green? Applicant 1:Street address missing
	Validation messages Names	Green? Applicant 1:Telephone No. missing
	Validation messages Names	Green? Applicant 1:Facsimile No. missing
	Validation messages Names	Green? Applicant (2) is also indicated as Inventor only (1). Please correct.
	Validation messages Names	Green? Applicant (3) is also indicated as Inventor only (2). Please correct.
13-2-4	Validation messages Priority	Green? No priority of an earlier application has been claimed. Please verify
13-2-7	Validation messages Contents	Yellow! The power of attorney or a copy of the general power of attorney will need to be furnished unless all applicants sign the request form.
13-2-9	Validation messages Payment	Yellow Deposit account number missing.
	Validation messages Payment	Green? Please ensure that you have a valid deposit account with the receiving Office selected.

Method and Apparatus to Support Booting Despite Deficient Resources

Field of the Invention

[0001] The present disclosure relates generally to the field of data processing, and more particularly to a method and related apparatuses to facilitate the process of booting a processing system despite resource deficiencies.

Background

[0002] A typical enterprise server platform includes a complex peripheral connect interface (PCI) subsystem. For example, the PCI subsystem may include multiple PCI root bridges and multiple on-board PCI-to-PCI bridges. With such a complex PCI hierarchy, it is likely for the end-user or administrator to install or connect a large number of PCI add-on devices, some of which might request large amounts of platform resources, such as memory mapped input/output (I/O) for example. As a result, on a processing system such as an enterprise server, it is not unusual for the PCI devices to demand more resources than the platform can provide. Moreover, this problem is not limited to enterprise servers, but may occur in other types of data processing systems.

[0003] In a conventional processing system, when the PCI devices request more resources than the platform can provide, the processing system cannot boot to an operating system (OS). Instead, the basic input/output system (BIOS) may simply return an error and then terminate without booting an OS.

Brief Description Of The Drawings

[0004] The features and advantages of the present invention will become apparent from the appended claims and the following detailed description of one or more example embodiments, in which:

[0005] FIG. 1 is a block diagram depicting an example embodiment of a suitable data processing environment in which certain aspects of the invention may be implemented;

[0006] FIG. 2 is a flowchart illustrating a process to support booting despite deficient platform resources, in accordance with one embodiment of the present invention; and

[0007] FIG. 3 is a block diagram depicting an example embodiment of the data processing environment of FIG. 1 after execution of the example process depicted in FIG. 2.

5 **Detailed Description**

[0008] The present disclosure describes one or more example embodiments of methods and apparatuses which support booting a processing system despite deficient resources in the processing system.

10 [0009] FIG. 1 and the following discussion are intended to provide a general description of a suitable environment in which certain aspects of the present invention may be implemented. As used herein, the terms "processing system" and "data processing system" are intended to broadly encompass a single machine, or a system of communicatively coupled machines or devices operating together. Exemplary processing systems include, without limitation, distributed computing systems,
15 supercomputers, computing clusters, mainframe computers, mini-computers, client-server systems, personal computers, workstations, servers, portable computers, laptop computers, tablets, telephones, personal digital assistants (PDAs), handheld devices, entertainment devices such as audio and/or video devices, and other devices for processing or transmitting information.

20 [0010] The data processing environment of FIG. 1, for example, may include a processing system 20 that includes one or more processors or central processing units (CPUs) 22 communicatively coupled to various other components via one or more system buses 32, 42, 52, and 62, or other communication conduits. Such components may include one or more volatile or non-volatile data storage devices,
25 such as random access memory (RAM) 30, read-only memory (ROM) 58, mass storage devices such as integrated drive electronics (IDE) hard drives 56 and 64, and/or other devices or media, such as floppy-disks, optical storage, tapes, flash memory, memory sticks, digital video disks, biological storage, etc. For purposes of this disclosure, the term "ROM" may be used in general to refer to non-volatile
30 memory devices such as erasable programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), flash ROM, flash memory, etc.

[0011] The components coupled to processor 22 in processing system 20 may also include one or more PCI root bridges 40 and one or more PCI-to-PCI bridges 50 and

60. One or more of the above bridges may be used to connect processor 22 with ROM 58 and hard drives 56 and 64, and with additional components, such as one or more of each of the following: a video controller 44, a small computer system interface (SCSI) controller 48, a network controller 54, a USB controller 66, and a universal serial bus (USB) keyboard 46. Some components, such as video controller 44 for example, may be implemented as adapter cards with interfaces, such as a PCI connector, for communicating with PCI bus 42.

[0012] In one embodiment, one or more devices may be implemented as embedded controllers, using components such as programmable or non-programmable logic devices or arrays, application-specific integrated circuits (ASICs), embedded computers, smart cards, and the like. For instance, PCI root bridge 40 may be implemented as an embedded device, residing on a system backplane or motherboard.

[0013] Processing system 20 may be controlled, at least in part, by input from conventional input devices, such as keyboards, mice, etc., and/or by directives received from another machine, interaction with a virtual reality (VR) environment, biometric feedback, or other input sources or signals. Processing system 20 may utilize one or more connections to one or more remote data processing systems 70, such as through network controller 54, through a modem, or through another communicative coupling. Processing systems may be interconnected by way of a physical and/or logical network 72, such as a local area network (LAN), a wide area network (WAN), an intranet, the Internet, etc. Communications involving network 72 may utilize various wired and/or wireless short range or long range carriers and protocols, including radio frequency (RF), satellite, microwave, Institute of Electrical and Electronics Engineers (IEEE) 802.11, Bluetooth, optical, infrared, cable, laser, etc.

[0014] The invention may be described by reference to or in conjunction with associated data including instructions, functions, procedures, data structures, application programs, etc. which when accessed by a machine result in the machine performing tasks or defining abstract data types or low-level hardware contexts. The data may be stored in volatile and/or non-volatile data storage.

[0015] For instance, in the illustrated embodiment, ROM 58 includes one or more instruction sets to support booting processing system 20 even if processing system 20

does not include sufficient resources to meet the resource requests of all devices within processing system 20. In the example embodiment, those instructions may reside partially or completely within a PCI bus driver 36, which may communicate with other software or firmware components, such as a PCI host bridge driver 34. During platform initialization, those instructions and other software or firmware may be copied from ROM 58 to RAM 30.

[0016] A model for an interface between platform firmware and higher-level software such as operating systems was recently announced. That model is known as the Extensible Firmware Interface (EFI). Version 1.10 of the EFI Specification, dated December 1, 2002, may be obtained from www.intel.com/technology/efi/main_specification.htm. The EFI specification defines a set of standard interfaces and structures to be provided by low-level platform firmware, for use in loading additional firmware and booting the OS. Platform frameworks based on the EFI model, such as the Intel® Platform Innovation Framework for EFI, are expected to supplant frameworks based on the BIOS model within the next few years as the frameworks of choice for designing, building, and operating data processing systems. The Intel® Platform Innovation Framework for EFI includes low-level firmware which provides boot and runtime service calls that are available to the operating system and its loader.

[0017] In the embodiment of FIG. 1, processing system 20 may use the Intel® Platform Innovation Framework for EFI. That framework provides distinct boot and runtime execution environments. Within the boot environment, the Intel® Platform Innovation Framework for EFI provides a class of services known as boot services. The boot services include various interfaces and protocols that provide an OS loader with access to platform capabilities required to complete OS boot. The boot services are also available to drivers and applications that need access to platform capability. However, the boot environment and thus the boot services are generally terminated once the operating system takes control of the platform. Within the runtime environment, the Intel® Platform Innovation Framework for EFI provides a class of services known as runtime services. The runtime services include interfaces that provide access to underlying platform-specific hardware that may be useful during OS runtime, such as timers. The runtime services are available during the boot process, but also persist after the OS loader terminates boot services.

[0018] Within the environment provided by the Intel® Platform Innovation Framework for EFI, each device may be uniquely identified by a device path. Also, the Intel® Platform Innovation Framework for EFI may maintain information in the pre-OS environment about devices needed or expected to be present when completing a boot process. For example, for the Intel® Platform Innovation Framework for EFI may maintain the following global variables to identify the following respective devices:

- ConIn: identifies the device path of the default input console device during boot;
- ConOut: identifies the device path of the default output console device during boot;
- ErrOut: identifies the device path of the default console device for outputting error messages during boot; and
- Boot### (e.g., Boot001, Boot002, etc.): identifies the device path for a boot device.

Also, boot device selection (BDS) refers to an architectural phase within the pre-OS environment. Variables such as those listed above may be referred to as architectural boot device variables, and they may be used during BDS to determine the console devices and boot devices needed to boot an OS.

[0019] PCI host bridge driver 34 may constitute platform-specific code that exposes unique platform features to PCI bus driver 36. PCI bus driver 36 may constitute generic, platform-neutral code whose operations conform with PCI specifications. For instance, a developer may create a single PCI bus driver 36 that is capable of working with many different kinds of platforms, including without limitation simple desktop systems and complex enterprise servers.

[0020] In an example embodiment, before processing system 20 enters the BDS phase, PCI bus driver 36 may retrieve boot device information from the pre-OS environment and use that information to facilitate successful booting in a resource deficient platform, as described in greater detail below.

[0021] FIG. 2 is a flowchart illustrating a process to facilitate booting in accordance with an example embodiment of the present invention. That process is described with regard also to FIG. 1. The process of FIG. 2 may begin with processing system 20 performing boot operations in a pre-OS environment, for example in response to being powered on or reset. In the example embodiment, the process of FIG. 2

begins after processing system 20 has instantiated an EFI driver execution environment (DXE) and loaded PCI host bridge driver 34 and PCI bus driver 36.

[0022] At block 110 PCI bus driver 36 scans the entire PCI hierarchy to discover all devices in the PCI subsystem. In conjunction with scanning the PCI subsystem, PCI bus driver 36 builds a data structure, such as a PCI device tree for example, to represent and identify the discovered topology of the PCI subsystem, as indicated at block 112. Such a data structure may also be referred to as a device map. For example, in accordance with the embodiment illustrated in FIG. 1, the device map may reflect the topology of the devices residing within PCI subsystem 80.

[0023] PCI bus driver 36 may also enumerate all of the devices in PCI subsystem 80 to collect the resource requests from those devices, as shown at block 114. PCI bus driver 36 may receive various different types of resource requests, such as bus number requests, memory requests, and I/O mapping requests, for example. PCI bus driver 36 may record the resource requirements for each device in the device map.

[0024] PCI bus driver 36 may then obtain information from PCI host bridge driver 34 indicating which resources are available to be allocated to the PCI devices, as indicated at block 116. As depicted at block 120, PCI bus driver 36 may then use the resource information from PCI host bridge driver 34 and the request information from the PCI devices to determine whether processing system 20 provide the resources needed to satisfy the resource requests of the PCI devices. If processing system 20 has sufficient resources, PCI bus driver 36 may select all of the PCI devices for the device pool and may allocate the requested resources to those devices, as indicated at blocks 122 and 124.

[0025] However, if processing system 20 contains insufficient resources to meet the requests, the process may pass from block 120 to block 130, which depicts PCI bus driver 36 determining which of the PCI devices are critical to the boot process. In the example embodiment, PCI bus driver 36 identifies the boot-critical devices by retrieving boot information from the EFI DXE. For example, PCI bus driver 36 may obtain device identifiers such as device path designations from EFI BDS variables such as ConIn, ConOut, ErrOut, Boot001, Boot002, etc. PCI bus driver 36 may then select the devices identified by those device paths for inclusion in the device pool, as

depicted at block 132. For instance, the device map may be updated to indicate that the boot-critical devices have been selected for the device pool.

[0026] In one embodiment, all devices identified by the ConIn, ConOut, ErrOut, and Boot### variables are selected as boot-critical devices. In addition, PCI bus driver 36 may identify certain intermediary devices, such as PCI-to-PCI bridges for example, as necessary to provide access to the boot-critical devices referenced above, based on the topology identified in the device map. PCI bus driver 36 may select those intermediate devices as boot-critical devices, as well. In alternative embodiments, different policies may be used to establish optimal or minimal resource requirements for the PCI subsystem.

[0027] PCI bus driver 36 may then finalize the list of devices to be allocated based on an appropriate allocation or rejection policy. As indicated at block 134 and 140, in the illustrated embodiment, PCI bus driver 36 may loop through a process of deselecting or rejecting one or more of the devices that were not identified as boot-critical, and then determining whether the platform provides sufficient resources for the remaining devices. PCI bus driver 36 may use the resource information from the PCI host bridge driver 34 and the request information in the device map to determine whether sufficient resources are available. According to one rejection policy, PCI bus driver 36 may deselect or reject devices in order of resource requirements, starting with the non-boot-critical device that would require the largest amount of resources. In another embodiment, the PCI bus driver may simply reject all devices not identified as boot-critical. Other policies may be used in alternative embodiments. In one embodiment, if the PCI bus driver has rejected all non-boot-critical devices and sufficient resources are still not available, the PCI bus driver may proceed to reject one or more boot-critical devices, using any appropriate rejection policy, until the remaining devices do not require more resources than the platform has available.

[0028] Once PCI bus driver 36 has identified the devices to be included in the device pool and either explicitly or implicitly deselected or rejected the remaining devices, including any appropriate intermediate devices, PCI bus driver 36 may disable all devices that weren't selected for the device pool, as shown at block 144. For instance, PCI bus driver 36 may disable rejected devices by modifying configuration

settings in the configuration space of those devices, to prevent those devices from receiving and reacting to PCI bus cycles.

[0029] PCI bus driver may allocate the requested resources for the devices that were selected for the device pool, as shown at block 124. The process for coping with possible resource deficiencies may then end, and processing system 20 may continue with a boot process, for example by completing any remaining operations associated with pre-OS system configuration and then entering the BDS phase and booting an OS.

[0030] Since the rejected devices may be excluded from the device pool and disabled, they may be hidden from device drivers and invisible to the OS, and the OS may be prevented from subsequently enabling the rejected devices. Nevertheless, certain types of diagnostics and debugging may be performed on the system, as diagnostic or debugging tools may be able to scan PCI subsystem 80 and diagnose all PCI devices in a system, including the rejected devices.

[0031] FIG. 3 is a block diagram depicting an example embodiment of the data processing environment of FIG. 1 after execution of the example process depicted in FIG. 2. As indicated by the diagonal slash marks, in an example implementation, PCI bus driver 36 may have rejected and disabled SCSI controller 48, network controller 54, and ROM 58. However, PCI bus driver 36 may have allocated resources for all boot-critical devices in PCI subsystem 80, including devices for ConIn, ConOut, Boot001, Boot002, and all required intermediary devices or bridges. For instance, in the illustrated embodiment, since USB keyboard 46 was designated as the ConIn device, both USB keyboard 46 and the associated USB controller 66 were identified as boot-critical devices. By contrast, in an implementation where USB keyboard 46 is not designated as the ConIn device, USB controller 66 and USB keyboard 46 may be rejected or disregarded when resources are allocated for PCI devices.

[0032] In accordance with the present disclosure, firmware or software in a processing system may identify critical and non-critical devices, allocate resources to the critical devices, and disable the non-critical devices, so that the processing system can boot to an OS despite insufficient resources to satisfy all of the devices. By contrast, when a legacy system includes more devices than the system can support, the system may be unable to boot to an operating system (OS), as described above.



[0033] In light of the principles and example embodiments described and illustrated herein, it will be recognized that the illustrated embodiments can be modified in arrangement and detail without departing from such principles. And, though the foregoing discussion has focused on particular embodiments, other configurations are contemplated. In particular, even though expressions such as “in one embodiment,” “in another embodiment,” or the like are used herein, these phrases are meant to generally reference embodiment possibilities, and are not intended to limit the invention to particular embodiment configurations. As used herein, these terms may reference the same or different embodiments that are combinable into other embodiments.

[0034] Similarly, although example processes have been described with regard to particular operations performed in a particular sequence, it will be apparent to those of ordinary skill in the art that numerous modifications to that process could be applied to derive numerous alternative embodiments of the present invention. For example, alternative embodiments may include processes that use fewer than all of the disclosed operations, processes that use additional operations, processes that use the same operations in a different sequence, and processes in which the individual operations disclosed herein are combined, subdivided, or otherwise altered.

[0035] Alternative embodiments of the invention also include machine accessible media encoding instructions for performing the operations of the invention. Such embodiments may also be referred to as program products. Such machine accessible media may include, without limitation, storage media such as floppy disks, hard disks, CD-ROMs, ROM, and RAM; as well as communications media such as antennas, wires, optical fibers, microwaves, radio waves, and other electromagnetic or optical carriers. Accordingly, instructions and other data may be delivered over transmission environments or networks in the form of packets, serial data, parallel data, propagated signals, etc., and may be used in a distributed environment and stored locally and/or remotely for access by single or multi-processor machines.

[0036] It should also be understood that the hardware and software components depicted herein represent functional elements that are reasonably self-contained so that each can be designed, constructed, or updated substantially independently of the others. In alternative embodiments, many of the components may be implemented

as hardware, software, or combinations of hardware and software for providing the functionality described and illustrated herein.

[0037] It should be noted, however, that the term "PCI" is not limited, for purposes of this disclosure, to the legacy PCI protocols and hardware, but also includes related protocols and hardware, such as PCI-X, PCI Express and other protocols, whether implemented before or after preparation of this disclosure. Furthermore, the invention is not limited to any particular hardware architecture, but may be practiced in association with a wide variety of architectures, including 32-bit architectures and 64-bit architectures.

[0038] In view of the wide variety of useful permutations that may be readily derived from the example embodiments described herein, this detailed description is intended to be illustrative only, and should not be taken as limiting the scope of the invention. What is claimed as the invention, therefore, is all implementations that come within the scope and spirit of the following claims and all equivalents to such implementations.

What is claimed is:

1. A method comprising:

determining, during a process of booting a processing system, whether
5 sufficient resources are available to meet resource requests for multiple devices
associated with a peripheral connect interface (PCI) subsystem of the processing
system;

retrieving boot information from an extended firmware interface (EFI)
environment of the processing system;

10 automatically identifying at least one of the multiple devices as boot-critical,
based on the boot information from the EFI environment; and

if sufficient resources to meet the resource requests are not available,
automatically allocating resources for the device identified as boot-critical but not for
all of the devices associated with the PCI subsystem, before the processing system
15 boots an operating system (OS).

2. A method according to claim 1, further comprising:

identifying at least one device associated with the PCI subsystem as not
critical to booting the processing system; and

20 disabling the device identified as not critical, before the processing system
boots the OS, if sufficient resources to meet the resource requests are not available.

3. A method according to claim 1, wherein the operation of retrieving boot
information from an EFI environment of the processing system comprises:

25 retrieving information that designates at least one device selected from a
group consisting of:

a device to serve as an input console during boot;

a device to serve as an output console during boot; and

a device to provide OS boot instructions.

4. A method according to claim 1, further comprising:
discovering the devices associated with the PCI subsystem by scanning the
PCI subsystem.

5 5. A method according to claim 1, further comprising:
collecting resource requests from at least two of the devices associated with
the PCI subsystem; and
determining whether sufficient resources are available, based on the collected
resource requests.

10 6. A method according to claim 1, further comprising:
determining available resources of the processing system, based on resource
information from a host bridge driver.

15 7. A method according to claim 6, wherein the operation of determining whether
sufficient resources are available to meet the resource requests comprises:
automatically determining whether sufficient resources are available, based
on the resource information from the host bridge driver.

20 8. A method according to claim 1, further comprising:
automatically identifying at least one of the devices associated with the PCI
subsystem to be rejected, based on a rejection policy.

9. A method according to claim 1, further comprising:

collecting resource requests from at least two of the devices associated with the PCI subsystem;

determining available resources of the processing system, based on resource information from a host bridge driver.

automatically determining whether sufficient resources are available for the devices associated with the PCI subsystem, based on the collected resource requests and the resource information from the host bridge driver; and

disabling at least one of the devices associated with the PCI subsystem before the processing system boots the OS, if sufficient resources are not available to meet the resource requests.

10. An apparatus comprising:

a processor;

a peripheral connect interface (PCI) subsystem communicatively coupled to the processor;

two or more devices associated with the PCI subsystem;

a machine accessible medium communicatively coupled to the processor;

and

a bus driver encoded in the machine accessible medium, wherein the bus driver, when executed by the processor, performs operations comprising:

determining, during a process of booting the processing system, whether sufficient resources are available to meet resource requests for the two or more devices;

retrieving boot information from an extended firmware interface (EFI) environment of the processing system;

automatically identifying at least one of the devices as boot-critical, based on the boot information from the EFI environment; and

if sufficient resources to meet the resource requests are not available, facilitating successful booting of an operating system (OS) by automatically allocating resources for the device identified as boot-critical but not for all of the devices associated with the PCI subsystem, before the processing system boots the OS.

11. An apparatus according to claim 10, wherein the bus driver performs further operations, comprising:

identifying at least one device associated with the PCI subsystem as not critical to booting the processing system; and

5 disabling the device identified as not critical, before the processing system boots the OS, if sufficient resources to meet the resource requests are not available.

12. An apparatus according to claim 10, wherein the bus driver retrieves boot information from the EFI environment designating at least one device selected from a group consisting of:

a device to serve as an input console during boot;

a device to serve as an output console during boot; and

a device to provide OS boot instructions.

13. An apparatus according to claim 10, wherein the bus driver performs further operations, comprising:

discovering the devices associated with the PCI subsystem by scanning the PCI subsystem.

14. An apparatus according to claim 10, wherein the bus driver performs further operations, comprising:

collecting resource requests from at least two of the devices associated with the PCI subsystem; and

determining whether sufficient resources are available, based on the collected resource requests.

15. An apparatus according to claim 10, wherein:

the apparatus further comprises a host bridge driver encoded in the machine accessible medium; and

the bus driver determines available resources of the processing system, based on resource information obtained from the host bridge driver.

16. An apparatus according to claim 15, wherein the bus driver automatically

determines whether sufficient resources are available, based on the resource information obtained from the host bridge driver.

17. An apparatus according to claim 10, wherein, if sufficient resources are not available, the bus driver automatically identifies at least one of the devices associated with the PCI subsystem to be rejected, based on a rejection policy.

18. An apparatus according to claim 10, wherein:
the apparatus further comprises a host bridge driver encoded in the machine accessible medium; and
the operations performed by the bus driver further comprise:
collecting resource requests from at least two of the devices associated with the PCI subsystem;
determining available resources of the processing system, based on resource information from the host bridge driver;
automatically determining, based on the collected resource requests and the resource information from the host bridge driver, whether sufficient resources are available for the devices associated with the PCI subsystem; and
disabling at least one of the devices associated with the PCI subsystem, before the processing system boots the OS, if sufficient resources are not available to meet the resource requests.

19. An apparatus comprising:
a machine accessible medium; and
instructions encoded in the machine accessible medium, wherein the instructions, when executed by a processing system, cause the processing system to perform operations comprising:
determining, during a process of booting the processing system, whether sufficient resources are available to meet resource requests for two or more devices associated with a peripheral connect interface (PCI) subsystem of the processing system;
retrieving boot information from an extended firmware interface (EFI) environment of the processing system;

automatically identifying at least one of the devices as boot-critical, based on the boot information from the EFI environment; and

if sufficient resources are not available to meet the resource requests, automatically allocating resources for the boot-critical device but not for all of the devices associated with the PCI subsystem, before the processing system boots an operating system (OS).

20. An apparatus according to claim 19, further comprising:

a bus driver encoded in the machine accessible medium, wherein the bus driver comprises the instructions.

21. An apparatus according to claim 19, wherein the operations performed by the instructions further comprise:

identifying at least one device associated with the PCI subsystem as not critical to booting the processing system; and

disabling the device identified as not critical, before the processing system boots the OS, if sufficient resources to meet the resource requests are not available.

22. An apparatus according to claim 19, wherein the operation of retrieving boot information from an EFI environment of the processing system comprises:

retrieving information that designates at least one device selected from a group consisting of:

a device to serve as an input console during boot;

a device to serve as an output console during boot; and

a device to provide OS boot instructions.

23. An apparatus according to claim 19, wherein the operations performed by the instructions further comprise:

discovering the devices associated with the PCI subsystem by scanning the PCI subsystem.

24. An apparatus according to claim 19, wherein the operations performed by the instructions further comprise:

collecting resource requests from at least two of the devices associated with the PCI subsystem; and

determining whether sufficient resources are available, based on the collected resource requests.

5

25. An apparatus according to claim 19, wherein the operations performed by the instructions further comprise:

determining available resources of the processing system, based on resource information from a host bridge driver.

10

26. An apparatus according to claim 25, wherein the operation of determining whether sufficient resources are available comprises:

automatically determining whether sufficient resources are available, based on the resource information from the host bridge driver.

15

27. An apparatus according to claim 19, wherein:

if sufficient resources are not available, the instructions automatically identify at least one of the devices associated with the PCI subsystem to be rejected, based on a rejection policy.

20

28. An apparatus according to claim 19, wherein the operations performed by the instructions further comprise:

collecting resource requests from at least two of the devices associated with the PCI subsystem;

25

determining available resources of the processing system, based on resource information from a host bridge driver;

automatically determining, based on the collected resource requests and the resource information from the host bridge driver, whether sufficient resources are available for the devices associated with the PCI subsystem; and

30

disabling at least one of the devices associated with the PCI subsystem, before the processing system boots the OS, if sufficient resources are not available to meet the resource requests.

ABSTRACT

A method and related apparatuses support booting despite deficient system
5 resources. In one embodiment, a processing system includes two or more devices
in a peripheral connect interface (PCI) subsystem, as well as instructions encoded in
a machine accessible medium. The instructions, when executed during a process of
booting the processing system, may determine whether sufficient resources are
available for the devices. The instructions may also retrieve boot information from an
10 extended firmware interface (EFI) environment of the processing system, and may
automatically identify a device as boot-critical, based on that boot information. The
instructions may also identify a device to be rejected, and may automatically allocate
resources for the boot-critical device but not for the rejected device, before the
processing system boots the OS, if sufficient resources for the devices are not
15 available. Other embodiments are described and claimed.

1/3




FIG. 1

2/3





FIG. 2



BEST AVAILABLE COPY

FIG. 3